



Produced by the United States Geological Survey
 Control by USGS, NOS/NOAA, and Louisiana Geodetic Survey
 Planimetry by photogrammetric methods from aerial photographs taken 1966. Topography by planetable surveys 1968
 Projection and 10,000-foot grid ticks: Louisiana coordinate system, south zone (Lambert conformal conic) 1000-meter Universal Transverse Mercator grid ticks, zone 15, shown in blue 1927 North American Datum (NAD 27)
 North American Datum of 1983 (NAD 83) is shown by dashed corner ticks. The values of the shift between NAD 27 and NAD 83 for 7.5-minute intersections are given in USGS Bulletin 1875.
 Fine red dashed lines indicate selected fence and field lines where generally visible on aerial photographs. This information is unchecked. This map covers a subsidence area. Evaluate relief and elevation information based on recent sources.

UTM GRID AND 1994 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET
 0° 38' 53" MILS

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS
 FOR SALE BY U.S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR RESTON, VIRGINIA 22092
 AND LOUISIANA DEPARTMENT OF TRANSPORTATION AND DEVELOPMENT, BATON ROUGE, LOUISIANA 70804
 A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

SCALE 1:24,000
 1000 0 1000 2000 3000 4000 5000 6000 7000 FEET
 1 KILOMETER

CONTOUR INTERVAL 5 FEET
 NATIONAL GEODETIC VERTICAL DATUM OF 1929

ROAD CLASSIFICATION
 Primary highway, hard surface
 Secondary highway, hard surface
 Interstate Route
 U.S. Route
 State Route
 Light-duty road, hard or improved surface
 Unimproved road

QUADRANGLE LOCATION
 LOUISIANA

KROTZ SPRINGS, LA.
 SE 1/4 PALMETTO 15' QUADRANGLE
 30091-E7-TF-024
 1968
 REVISED 1994
 DMA 7645 III SE-SERIES V885